

ULTRABAKE™ SHEETING 315°C



- Can be supplied in sheet form or custom die cut
- Recommended for Powder Coating, E-Coating, Plating and Anodising
- Sheeting can be used for gaskets, pads, strips, washers and seals
- Reusable and durable

Part Number	Size (mm)	
	Length/Width	Thickness
US031-36	915mm x 915mm	0.79
US062-36	915mm x 915mm	1.58
US093-36	915mm x 915mm	2.36
US125-36	915mm x 915mm	3.18
US187-36	915mm x 915mm	4.75
US250-36	915mm x 915mm	6.35
US375-36	915mm x 915mm	9.53
US500-36	915mm x 915mm	12.70


ULTRABAKE™ CORD 315°C



- Recommended for Powder Coating, E-Coating, Plating and Anodising
- Ideal for slots and through holes
- Flexible and reusable

Part Number	Diameter (mm)	Coil Length (mtrs)
UC0070	1.78	30
UC0093	2.36	30
UC0103	2.62	30
UC0125	3.18	30
UC0139	2.53	30
UC0156	3.96	30
UC0187	4.75	30
UC0210	5.33	30
UC0250	6.35	30
UC0275	6.99	30
UC0312	7.93	30
UC0375	9.53	15
UC0437	11.10	15
UC0500	12.70	15
UC0562	14.28	15

ULTRABAKE™ STAR TUBING 315°C



- Protects threads, one size fits several diameters

Part Number	Colour	Min/Max dia (mm)	Coil Length (Mtrs)
UST-0500	Rusty Red	12.70-15.88	15
UST-0750	Blue	19.05-22.23	15
UST-1000	Green	25.40-30.48	15
UST-1500	Rusty Red	38.10-44.45	15

ULTRABAKE™ TUBING

315°C

Part Number	Thread Size	I.D. (mm)	O.D. (mm)	Coil Length (mtrs)
ST0040		1.02	4.19	30
ST0062		1.58	4.75	30
ST0080		2.03	5.21	30
ST0093		2.36	5.54	30
ST0109	M3	2.77	5.94	30
SRR-M3 (Blue)	M3	2.87	5.32	30
ST0125		3.18	6.35	30
ST0140		3.56	6.73	30
SRR-M4 (Green)	M4	3.87	6.34	30
ST0156	M4	3.96	7.14	30
ST0172		4.37	7.54	30
ST0187	M5	4.75	7.93	30
SRR-M5 (Mauve)	M5	4.87	7.10	30
ST0203		5.16	8.33	30
ST0218		5.54	8.71	30
SRR-M6 (Black)	M6	5.87	8.70	30
ST0234	M6	5.94	9.37	30
ST0250		6.35	9.53	30
ST0281		7.14	10.31	30
SRR-M8 (White)	M8	7.49	10.35	30
ST0312	M8	7.93	11.10	30
ST0343		8.71	11.89	30
ST0375	M10	9.53	12.70	30
SRR-M10 (Brown)	M10	9.87	12.75	30
ST0406		10.31	13.49	30
ST0437		11.10	14.28	30
ST0500		12.70	15.88	30
ST0625		15.88	19.05	15
ST0750		19.05	22.23	15
ST0875		22.23	25.40	15
ST0937		23.80	26.98	15
ST1000		25.40	28.58	15
ST1125		28.58	31.75	15
ST1250		31.75	34.93	15
ST1375		34.93	38.10	15
ST1500		38.10	41.28	15
ST1625		41.28	44.45	15
ST1750		44.45	47.63	15
ST1875		47.63	50.80	15
ST2000		50.80	53.98	15



- Recommended for Powder Coating, E-Coating, Plating and Anodising
- 1.59mm wall thickness
- Ideal for long studs and pins
- Flexible and reusable
- Extremely versatile – can be cut to required length
- Available as cut sleeves See below
- Larger diameters available on request
- Tubing also available in lower temperatures

CUT SLEEVES

260°C

Part Number	Colour	Thread Size	ID (mm)	Length (mm)	Quantity per Bag
SRS-M3	Blue	M3	2.87	40	100
SRS-M4	Green	M4	3.87	40	100
SRS-M5	Mauve	M5	4.87	40	100
SRS-M6	Black	M6	5.87	50	100
SRS-M8	White	M8	7.49	50	100
SRS -M9	Yellow	M9	8.87	50	100
SRS-M10	Brown	M10	9.87	50	100

- Metric sizes
- Colour coded
- Economical order quantities